


GH466 六层钢丝缠绕软管

超过 SAE100 R15



GH466-24

31.8 mm (1.25 in)
DN20

Dura-Tuff

EN856 / ISO18752

420 BAR (6100 PSI)

-40°C to +121°C
-40°F to +250°F

65

结构: 合成橡胶内层，四层高强度钢丝缠绕增强层，Dura-Tuff™ 高耐磨合成橡胶外层。

PART #	SIZE DIMENSIONS				PRESSURE				BEND		WEIGHT	
	Hose I.D.		Hose O.D. (nominal)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
GH466-20	31.8	1.25	49.3	1.94	420	6,090	1,680	24,400	420	16.50	3.48	2.34
GH466-24	38.1	1.50	57.4	2.26	420	6,090	1,680	24,400	510	20.80	4.63	3.11
GH466-32	50.8	2.00	71.7	2.82	420	6,090	1,680	24,400	630	24.80	6.70	4.47

工作温度范围: -40°C 到 +121°C (-40°F 到 +250°F)

应用:

适用于峰值压力高的压力系统。适用于石油基或水基液压油。如有其它特殊应用需求，请联系 Danfoss。